

# B6756 MACHINE PROTECTION DLG CERTIFIED SIO-LINE

## PVC FABRIC

### APPLICATIONS

Ideal for machine protection, water bladder, pillow tanks and all applications where contact with water is required.

<b>Roll Width</b>	245cm
<b>Roll Length</b>	50 metres
<b>Nominal Weight</b>	1400gsm
<b>Thickness</b>	1.15mm
<b>Fabric Type</b>	PES & PVC
<b>Finish</b>	Top: Gloss Bottom: Semi gloss
<b>Base Fabric</b>	Warp: PES 1100 dtex Weft: PES 1670 dtex
<b>Colours</b>	Yellow, Light Grey & Black
<b>Breaking Strength</b> (ISO 1421/1:2016)	Warp: 6000 N/50mm Weft: 6000 N/50mm
<b>Tear Strength</b> (DIN 53363:2003)	Warp: 1200N Weft: 1200N
<b>Adhesion</b> (ISO 2411:2017)	125 N/50mm
<b>Temperature Resistance</b> (EN 1876/1:1998)	-30/+70oC
<b>Light Fastness</b> (ISO 105 B02:2014)	7-8
<b>Treatment</b> (ISO 3795:1989)	100mm/min

**SIOEN sio-line®**